Wide Angle Reflecting Target

ZERO220 PLUS









The Undiscovered Potential

in a Compact Body

Prism Constant 0mm

The prism constant of ZERO220 is 0mm. It prevents from measuring in error.



Perfect Prism Position

Perfect Prism Placement brings an accurate and stable surveying.



Built-in Circular Level

While surevying, it is easy to check the level by built-in circular level 40' /2mm.



View Port

For accurate measuring, the prism center height is checkable from back.



Specific Coating

Z-220P has the specific coating for anti-diffuse refelection.



Repairable Independent Prism

Each prism is independent. In case the prism is broken, it is repairable at a minimum loss.






Smallest Class




Various Instruments Acceptable




Targetable Range





Prism Height



Specifcations

Prism Constant: 0mm

Size : W45×D65×H50mm

Weight : 137g Circular Level : 40' /2mm

Option

Spigot type Pole Adapter LSP100



| 5 | eι | Cor | iter | านร |
|---|----|-----|------|-----|
| | | | | |

- Z-220P
- Prism Protection Cover
- Shoe Tip DMP-M6
- Pole Adpater MAG50Hegonal Wrench
- Carrying Case
- Manual



| Code No. | Product Name | Model |
|----------|--------------------------------|--------|
| 222305 | Wide Angle Reflecting Target | Z-220P |
| 222281 | Spigot Type Pole Adapter 100mm | LSP100 |

Myzox Co., Ltd.

401 Yamagoe, Nagakute, Aichi 480-1111 Japan TEL: +81-561-64-2210 FAX: +81-561-63-7770

www.myzoxjapan.com

Your authorized dealer is :